

Items	Pre-ride Check ☒ P. 43	Frequency *1						Annual Check	Regular Replace	Refer to page
		× 1,000 km	1	12	24	36	48			
		× 1,000 mi	0.6	8	16	24	32			
Fuel Line	🔧			I	I	I	I	I		-
Fuel Level		I								-
Throttle Operation	🔧	I		I	I	I	I	I		79
Air Cleaner *2	🔧				R		R			-
Crankcase Breather *3				C	C	C	C			80
Spark Plug	🔧				R		R			-
Valve Clearance	🔧				I		I			-
Engine Oil		I	R	R	R	R	R	R		63
Engine Oil Filter			R		R		R			63
Engine Idle Speed	🔧			I	I	I	I	I		-
Radiator Coolant *4		I		I	I	I	I	I	3 Years	65
Cooling System	🔧			I	I	I	I	I		-
Secondary Air Supply System	🔧				I		I			-
Evaporative Emission Control System*5	🔧				I		I			-

Maintenance Level

- 🔧 : Intermediate. We recommend service by your dealer, unless you have the necessary tools and are mechanically skilled. Procedures are provided in an official Honda Shop Manual.
- 🔧 : Technical. In the interest of safety, have your motorcycle serviced by your dealer.

Maintenance Legend

- I : Inspect (clean, adjust, lubricate, or replace, if necessary)
- R : Replace
- L : Lubricate
- C : Clean

Maintenance Schedule

Items	Pre-ride Check P. 43	Frequency *1						Annual Check	Regular Replace	Refer to page	
		× 1,000 km	1	12	24	36	48				
		× 1,000 mi	0.6	8	16	24	32				
Drive Chain	I		Every 1,000 km (600 mi): I L								71
Drive Chain Slider				I	I	I	I			75	
Brake Fluid *4	I			I	I	I	I	I	2 Years	67	
Brake Pads Wear	I			I	I	I	I	I		68	
Brake System				I	I	I	I	I		43	
Brakelight Switch				I	I	I	I	I		69	
Headlight Aim				I	I	I	I	I		81	
Lights/Horn	I									–	
Engine Stop Switch	I									–	
Clutch System	I			I	I	I	I	I		76	
Side Stand	I			I	I	I	I	I		70	
Suspension				I	I	I	I	I		–	
Nuts, Bolts, Fasteners				I	I	I	I	I		–	
Wheels/Tyres	I			I	I	I	I	I		51	
Steering Head Bearings				I	I	I	I	I		–	

Notes:

*1 : At higher odometer reading, repeat at the frequency interval established here.

*2 : Service more frequently when riding in unusually wet or dusty areas.

*3 : Service more frequently when riding in rain or at full throttle.

*4 : Replacement requires mechanical skill.

*5 : ED, E type only